

CPAT® DRV3 / DSG1

// Portable Digital Leakage Detector / Digital Signal Generator

The DRV3 is a portable signal leakage detection meter designed to operate in all-digital and hybrid cable networks. It operates as a portable find-and-fix meter and as a monitoring probe when part of the CPAT FLEX system.

The DSG1 is a dual-band digital signal generator that inserts a low level digital signal between QAMs, without causing interference or MER degradation.

- High performance find-and-fix leakage meter for all-digital systems
- Fully agile from 118-140 MHz (Mid-band) and from 572-960 MHz (LTE-band)
- Patent pending technology using low level digital carrier
- No MER/BER impairment to adjacent QAM carriers
- Locates leakage in overbuild cable plants
- Based on our CPAT FLEX leakage monitoring system technology

// Leakage in all-digital networks

The DRV3 is your all-digital leakage monitoring and portable find-and-fix meter. With its dual-tuner design, the DRV3 simultaneously detects leakage in the Mid-band and in the LTE-band.

// Overbuild networks

The DRV3/DSG1 can be configured to use AM tag signature to discriminate between overbuild networks.

// Easy configuration

Your DRV3 meter can be configured via the front panel buttons. When operating with the ARD4, the DRV3 and DSG1 configurations are set through the CPAT Web application.



// Scalable solution

The DRV3 can be used in every vehicle as a find-and-fix leakage repair meter or as a leakage monitoring receiver when connected to the ARD4 recording device.

Using the ARD4/DRV3 package as a leakage monitoring/repair system gives you a flexible, cost-effective solution for your cable leakage control program of your all-digital networks.

effigis

// Specifications

// DSG1

// Electrical

Modulator type	Dual-band digital signal modulator
Frequency range output 1 of 2	Agile from 118 to 140 MHz (Mid-band)
Frequency range output 2 of 2	Agile from 572 to 960 MHz (LTE-band)
Frequency stability	Mid-band: ± 500 Hz LTE-band: ± 2.5 kHz
Tuning resolution	1 kHz
Modulated signal	10 to 110 Hz AM tag
Output level from each RF output	from +10 to 50 dBmV
Status display	Through an LCD on front panel
Communication port	10/100Base-T Ethernet
Setup	Through CPAT interface
Power	120 VAC, 0.5A (15W) fully loaded

// Physical

Dimensions	Standard 1RU chassis 4.4 cm x 21 cm x 33 cm / 1.75" x 8" x 13" [H x W x D]
Operating temperature	-20° to +60° C / -4° to +140° F

// Ordering Information

P/N

DRV3 – Digital Leakage Receiver Kit	150-00031-752
Includes:	
DRV3 – Digital Leakage Receiver	150-00031-001
Rubber ducky antenna (118-140 MHz)	111-00022-001
Rubber ducky antenna (698-806 MHz)	111-00007-001
110-220 VAC to 12 VDC Adaptor	110-00005-001
+12 VDC power supply	110-00010-001
Uni-flex mount for DRV3 dock station	012-00020-001
DRV3 - Dock station	150-00032-001
Battery pack	008-00002-001
DRV3 User Manual	100-00001-001

// Accessory Options

Rubber ducky antenna (806-866 MHz)	111-00008-001
Rubber ducky antenna (821-902 MHz)	111-00020-001
Rubber ducky antenna (902-960 MHz)	111-00025-001
Vehicle Magnetic-mount antenna BNC (118-140 MHz)	112-00004-100
Vehicle Magnetic-mount antenna SMA (572-960 MHz)	112-00009-100

// Related Items

ARD4 – WiFi Autonomous Recording Device Kit	150-00020-100
ARD4/DRV3 USB interconnect cable	036-00020-001

// DRV3

// Electrical

Detector type	Dual-band digital receiver/demodulator
Frequency range	Agile from 118 to 140 MHz (Mid-band) Agile from 572 to 960 MHz (LTE-band)
Channel tuning	Configurable via USB port and by front panel buttons
Tuning resolution	1 kHz
Level range	2 to 2,000 μ V/m @ 3 meters (Mid-band), 5 μ V/m to 2,000 μ V/m @ 3 meters (LTE-band)
Level accuracy	± 1.5 dB Mid-Band ± 2.5 dB LTE-Band
System tag	AM modulation 10-110 Hz
Audible tone	Yes, varies with leak intensity
Adjustable audio volume	Yes, variable
RF level scale display	Single scale from 0 to 2,000 μ V/m
Measurement units	μ V/m and dBuV/m
Power	Pack of 2 rechargeable Li-ion cells, 3,100 mAh
Operation time	2.5 hours nominal (both tuners activated) or 4.0 hours nominal (one tuner activated)
Charging temperature	0° to +45° C / 32° to +110° F
Communication port	USB serial port

// Physical

Dimensions	21 cm x 11 cm x 4 cm / 8.3" x 4.3" x 1.6" [H x W x D]
Weight	850 g / 30 ounces

// Dock station

Dimensions	24 cm x 12.5 cm x 8 cm / 9.4" X 4.9" X 3.2" [H x W x D]
Weight	240 g / 9 ounces

* Specifications subject to change without prior notice.

effigis 
GEO SOLUTIONS

4101 Molson Street, Suite 400,
Montreal, QC, Canada H1Y 3L1
+1-888-495-6577
effigis.com